



Global Corrosion Solutions Ltd
26 Kings Hill Avenue
West Malling
Kent
ME19 4AE
t: +44 (0) 8451 308 803
e: sales@neutrarustuk.com
w: www.neutrarustuk.com

Description

An acrylic based masonry finish, designed to offer long term protection and decoration.

Uses

Global Masonry Coat is the ideal product for protecting masonry when ultimate protection is needed without losing decorative appeal. Particularly used in industry for rendered areas of structures, you can be sure this product will not let you down.

Application

Ensure surface to be painted is sound, clean, dry and free from grease. Remove all mould and lichen and treat affected areas with sterilization wash.

WB masonry paint can be applied directly over bare and previously painted surfaces provided these are clean, sound and firm.

Chalky, under-bound surfaces, such as old cement-based paint and limewash, should be scraped, dry brushed and then given a coat of stabilizing primer. Before applying stabilizing primer to the whole surface, first carry out a test application to a small area. If this dries to a glossy film, thin with one part of white spirit to two parts of stabilizing primer and then test again in another small area. If a glossy film still results, try a blend of equal parts of white spirit and stabilizing primer. It is important to ensure that a NON-GLOSSY DRIED SEALED SURFACE IS PRODUCED.

Stir well before use. Do not thin, except for absorbent surfaces, when a small quantity of clean water may be added. Apply two full coats, allowing 4 to 6 hours between coats under normal drying conditions. Do not apply when air or surface temperatures are below 5oC, or when rain is imminent.

Material	WB Masonry Paint
Type of Material -	Acrylic Resin
Colour -	Selected range
Finish -	Matt
Theoretical Spreading Rate -	10 sq.metres / litre
Drying Times at 20 oC	
Touch Dry	2 Hours
Hard Dry -	2-4 Hours
Overcoating Interval	4 Hours
Application	Brush, Roller, conventional and Airless

Spray

Substrate -
etc.

Brick, Plaster, Concrete, Stone, Cement,

Flash Point

Not applicable

Thinning Solvent -
Cleaning Solvent -

Clean water
Clean water

Storage Life -

24 Months minimum

Minimum Ambient Application
Temperature

5 °C

Before using this product, read the label on the container and consult the material safety data sheet.

This data sheet is for general guidance only. The information is believed to be accurate at time of printing. However, it is given without obligation.